




eSHINE STREET 20 – Technical data

Model	Watt	Volt	Amp	Lumens	IP rating	Warranty	Dimensions HxWxD (mm)	Colour	LED Life expect.
eSS 20	20W	12V	1.66A	2,400	IP65	2 Yrs	585x380x122	6,500	50,000+hrs
eSS 40	40W	24V	1.66A	4,800	IP65	2 Yrs	637x380x122	6,500	50,000+hrs
eSS 60	60W	24V	2.50A	7,200	IP65	2 Yrs	637x380x122	6,500	50,000+hrs
eSS 80	80W	24V	3.33A	8,800	IP65	2 Yrs	637x380x122	6,500	50,000+hrs
eSS 100	100W	110-240		12,500	IP65	2 Yrs	637x380x122	6,500	50,000+hrs





Web: www.solarconcepts.com.au




Housing:	High Pressure Die Cast
Spigot:	50 /60mmOD
Lamp:	20watt High Powered LED
Warranty:	Housing: 10 years
Lamp:	1 year
Driver:	3 years

eSHINE STREET – 20 Photometric Results

Name:	eSHINE STREET 20		
Number:	2010020101	Diameter:	0 mm
Report:	ROADWAY LANTERN TEST	Length:	620 mm
Test no.:	NO.1	Width:	350 mm
Lamp type:	20Pcs Cree XP-E	Height:	122 mm
No. of lamps:	1	Power:	27.34 W
Lamp flux:	2400.00 lm	Operator:	C.H
Date:	01/02/2010 16:46:09	LOR:	83.6 %
Comment:	THE TEST RESULT IS FROM GONIOPHOTOMETER GO-DS1600		

ISOLINE diagram eSHINE STREET 20 / H0 to 355R - V0 to 180U



Luminaire mounting height above ground: 5m

Luminaire rotation angle: 0 º

eSHINE STREET – 20 Photometric Results

Name:	eSHINE STREET 20		
Number:	2010020101	Diameter:	0 mm
Report:	ROADWAY LANTERN TEST	Length:	620 mm
Test no.:	NO.1	Width:	350 mm
Lamp type:	20Pcs Cree XP-E	Height:	122 mm
No. of lamps:	1	Power:	27.34 W
Lamp flux:	2400.00 lm	Operator:	C.H
Date:	01/02/2010 16:46:09	LOR:	83.6 %
Comment:	THE TEST RESULT IS FROM GONIOPHOTOMETER GO-DS1600		

POLAR diagram eSHINE STREET 20 / H0 to 355R - V0 to 180U

